

1、性能指标

谐振频率	高斯贝尔数码科技股份有限公司 GOSPELL DIGITAL TECHNOLOGY CO., LTD $1.890 \text{ MHz} \pm 5 \text{ MHz}$		
介电常数 ϵ_r	介质: 37 ± 0.5		
品质因数Q值	> 5000 (华为提供的镀银腔体)		
温漂系数	$4 \pm 1 \text{ PPM}/^\circ\text{C}$		

2、结构特性 (单位: mm)

介质外径D	$\phi 13.3 \pm 0.1$	介质高度H	26.3 ± 0.1
介质内径d	$\phi 7.2 \pm 0.2$		

产品结构图:	<p>The drawing shows a cylindrical component. The top view is a circle with an outer diameter labeled 'D' and an inner diameter labeled 'd'. The side view is a cylinder with a total height labeled 'H'. The inner part of the cylinder is shown with diagonal hatching, indicating it is a hollow or a different material. The drawing is centered on a vertical axis.</p>		
--------	--	--	--

3、工作及储存环境

工作温度	$-40 \sim +90^\circ\text{C}$
储存环境	应储存在通风、干燥、清洁并无腐蚀性气体的库房内, 温度 $-10 \sim +40^\circ\text{C}$, 相对湿度 $45\% \sim 75\%$